



ELECTRICAL RESEARCH AND DEVELOPMENT ASSOCIATION
 (Accredited by the National Accreditation Board for Testing and Calibration Laboratories, Govt. of India)
 ERDA Road, Makarpura Industrial Estate, Vadodara-390 010, India.
 EPABX : +91 (0265) 2642942, 2642964, 2642377, 3043128 / 29 / 30 / 31 / 33
 Fax : +91 (0265) 2638382
 E-mail : erda@erda.org
 Web : http://www.erda.org




TEST REPORT

SHEET 1 OF 34

NAME AND ADDRESS OF CUSTOMER: Ashida Electronics Pvt. Ltd., Plot No. A-308, Road No.21, Wagle Industrial Estate, Thane-400604 Maharashtra, India.	REPORT NO.: RP-1617-049429	
	DATE : 24/01/2017	
	CUSTOMER REF. NO.: Nil	
	DATED: 12/01/2017	
	DATE OF SAMPLE RECEIPT	DATE OF TESTING
	12/01/2017	19/01/2017
SAMPLE DESCRIPTION: See Annexure-I Sheet No.2 of this report	SAMPLE IDENTIFICATION: See Annexure-I Sheet No.2 of this report	
TEST DETAILS Electrical fast transient	TEST SPECIFICATION: As per customer requirements & Procedure Followed as per Cl. No.7.2.5 of IEC 60255-26:2013	
Notes:		
1) Only Electrical Fast Transient/Burst immunity test has been carried out as per customer requirements.		
2) Transient were applied on port mentioned on Annexure: II of this test report.		
3) Operating procedure/conditions during the test & performance/acceptance criteria of the sample under test as specified by the customer are mentioned on sheet no.3, 4 & 5 of this test report.		
4) Detailed operating & test procedure of the ports & performance criteria during the test mentioned on sheet No. 6 & 7 of this test report.		
5) The list of the major equipments used during the test is mentioned on sheet no.9 of this report.		
6) Test set up block diagram is shown on sheet no.10 of this test report.		
7) Photograph of test set up and sample description mention on EUT is shown on sheet no.33 & 34 of this test report.		
REMARK: The sample conforms to the requirement as specified by the customer for the above-mentioned test.		
WITNESSED BY: Mr. Prashant Patil - Ashida Electronics Pvt. Ltd., Thane.		
<i>T Shushk</i> PREPARED BY	<i>Patil</i> CHECKED BY	<i>Vinod Gupta</i> APPROVED BY

- Notes:** 1.This report relates only to the particular sample received for testing in good condition at ERDA, Vadodara.
 2. This report can not be reproduced in part under any circumstances.
 3. Publication of this report requires prior permission in writing from the Director, ERDA.
 4. Only the test asked for by the customer have been carried out.
 5. In case of any dispute, Vadodara will be the exclusive jurisdiction & shall be construed as where the cause has arised.

Caution: ERDA is not responsible for the authenticity of photocopied or reproduced test reports.
 ERDA provides support to customer for verification of the authenticity of test reports issued by ERDA.



TL 1424167



Certificate No. : T-3359

ELECTRICAL RESEARCH AND DEVELOPMENT ASSOCIATION

(Accredited by the National Accreditation Board for Testing and Calibration Laboratories, Govt. of India)

ERDA Road, Makarpura Industrial Estate, Vadodara-390 010, India.

EPABX : +91 (0265) 2642942, 2642964, 2642377, 3043128 / 29 / 30 / 31 / 33

Fax : +91 (0265) 2638382

E-mail : erda@erda.org

Web : http://www.erda.org



TEST REPORT NO.: RP-1617-049429

DATE: 24/01/2017

SHEET 2 OF 34

ANNEXURE-I

SAMPLE DESCRIPTION:	SAMPLE IDENTIFICATION:
ASHIDA Feeder Protection Relay CT : 1A / 5A PT : 63.5 VAC Freq.: 50 Hz / 60 Hz Aux Supply = 24 V to 230 V AC/DC	Sr. No: 16L245M0001 Platform: ADR24xB-M ERDA Sample Code No.: ERDA-00177845
Accessories used: <ul style="list-style-type: none">• Doble - Model no.:F6150, Sr. No.: 060803068• Laptop	PREPARED BY <i>T. Shrestha</i>
CHECKED BY <i>[Signature]</i>	

TL 1424168





Certificate No. : T-3359

ELECTRICAL RESEARCH AND DEVELOPMENT ASSOCIATION

(Accredited by the National Accreditation Board for Testing and Calibration Laboratories, Govt. of India)

ERDA Road, Makarpura Industrial Estate, Vadodara-390 010, India.

EPABX : +91 (0265) 2642942, 2642964, 2642377, 3043128 / 29 / 30 / 31 / 33

Fax : +91 (0265) 2638382

E-mail : erda@erda.org

Web : http://www.erda.org



TEST REPORT NO.: RP-1617-049429

DATE: 24/01/2017

SHEET 3 OF 34

Operating procedure of the sample under test as specified by the customer:

Sample / Equipment under Test (EUT)

EUT: Feeder Protection Relay

EUT Brief Description:

The EUT is a high performance Enhance Aditya M (Modular) protection relay platform, designed for highly electrical noisy substation environment. Following are some of the feature of this platform:

- High performance 32-Bit processor with Floating point Unit operating at 200MHz
- 8 Analogue input having 16 bit simultaneous sampling ADC, design for CT or PT
- 32 Digital Input / Output extended up to 64 Nos.
- RTD and 4-20mA analogue input
- Dual redundant Ethernet ports
- RS485 port
- 16 dual colour LEDs
- Breaker Close / Trip Push buttons
- Graphical Display

Operating Procedure:

Connect the Input supply 110V DC to the power supply terminal of EUT.

Pick up value Test:

- Connect current source at 1A current to input terminal.
- Set current setting value to 100% i.e. 1A, TMS at Minimum (x0.02) value and Curve setting to C1.
- Start current injector & increase current value till relay get pick up and trip.
- The operating value should be within 1 to 1.1 times of set pickup value.

Operating Time Test:

- Set current 2N i.e. 2A and connect trip contact to timer.
- Change the TMS setting at 1.00.
- Start the current injector and measure the operating time. The trip time value should be within $\pm 12.5\%$ of actual value. (Actual time 10.029 Sec.)

PREPARED BY

T Shrestha

CHECKED BY

Arvind



TL 1424906



Certificate No. : T-3359

ELECTRICAL RESEARCH AND DEVELOPMENT ASSOCIATION

(Accredited by the National Accreditation Board for Testing and Calibration Laboratories, Govt. of India)

ERDA Road, Makarpura Industrial Estate, Vadodara-390 010, India.

EPABX : +91 (0265) 2642942, 2642964, 2642377, 3043128 / 29 / 30 / 31 / 33

Fax : +91 (0265) 2638382

E-mail : erda@erda.org

Web : http://www.erda.org



TEST REPORT NO.: RP-1617-049429

DATE: 24/01/2017

SHEET 4 OF 34

Operating procedure of the sample under test as specified by the customer:

Continued....

Operating condition during the test:

- EUT shall be in "ON" condition during the test.
- Applied 110 VDC to Auxiliary supply input terminal.
- Applied 63.5 VAC to PT input terminals.
- During test, Set Current value less than trip value (<90%). i.e.0.9 A
- All Binary inputs are energized with 110V DC.
- RS485 communication will be in working condition.

Performance Criteria as specified by customer :

Following parameters should be monitored Before, During & After the test.

- 'ENABLE' LED (Green) should be continuously 'ON'.
- Display of EUT should not garbage, reset and hang-up.
- All programmable LEDs (15 Nos. dual color) should remain OFF.

Following parameters of EUT should be checked before & after the test.

	A Ph. Value	B Ph. Value	C Ph. Value	Earth	Tolerance
Pick Up					1-1.1 Amp
Operating Time (2 Amp)					8.77-11.29 Sec

Notes:

- During performance test of EUT, measured value shall be observed on Relay test unit (Doble)/Laptop.
- Relay shall be considered to be stable subject to fulfillment of the performance criteria as specified by the customer.

PREPARED BY

Tshush

CHECKED BY

[Signature]

TL 1424450





Certificate No. : T-3359

ELECTRICAL RESEARCH AND DEVELOPMENT ASSOCIATION

(Accredited by the National Accreditation Board for Testing and Calibration Laboratories, Govt. of India)

ERDA Road, Makarpura Industrial Estate, Vadodara-390 010, India.

EPABX : +91 (0265) 2642942, 2642964, 2642377, 3043128 / 29 / 30 / 31 / 33

Fax : +91 (0265) 2638382

E-mail : erda@erda.org

Web : http://www.erda.org



TEST REPORT NO.: RP-1617-049429

DATE: 24/01/2017

SHEET 5 OF 34

Acceptance criteria 'B' as per Table 23 of IEC 60255-26:2013 & acceptance criteria 'B' as per Tables 4 & 6 respectively item no.4.2 & 6.2 of IEC 60255-26:2013

Function	Conditions for acceptance	As specified by customer
Protection	Normal performance within the specification limits, during and after the test	<ul style="list-style-type: none"> The relay should remain stable during the test. No false indication should be observed on EUT before, during and after the test.
Command and control	Normal performance within the specification limits, during and after the test	<p>'Non-operate' condition:</p> <ul style="list-style-type: none"> Before, during and after the test, assigned general pick up contact output 3 should not operate, which shall be checked through trip LED. (i.e. LED should be OFF)
Measurement	Temporary degradation during the test, with self-recovery at the end of the test. No loss of store data.	<ul style="list-style-type: none"> The operating value should be within 1 to 1.1 times of set pickup value before & after the test. The trip time value should be within $\pm 12.5\%$ of actual value. (Actual time 10.029 Sec.) before & after the test.
Integral human-machine interface and visual alarms	Temporary degradation or loss of function during the test, with self-recovery at the end of the test. No loss of store data.	<p>'Non operate' condition :</p> <ul style="list-style-type: none"> ENABLED LED should be continuously 'ON' & all other LEDs should be 'OFF' before, during and after the test.
Data communication ^b	Possible bit error rate increase but no loss of transmitted data.	Not applicable
Binary input, binary output and output contacts	No unwanted change of status is allowed during the test ^a .	<p>'Non-operate' condition:</p> <ul style="list-style-type: none"> Before, during and after the test, assigned general pick up contact output 3 should not operate, which shall be checked through trip LED. (i.e. LED should be OFF)

a For binary input the manufacture shall state the minimum filtering value for which the test was successful.

b Excluding communication ports for protection or control functionality. For those acceptance criteria see protection or command and control.

PREPARED BY

CHECKED BY

T. Bhus

allie

TL 1424171





Certificate No. : T-3359

ELECTRICAL RESEARCH AND DEVELOPMENT ASSOCIATION

(Accredited by the National Accreditation Board for Testing and Calibration Laboratories, Govt. of India)

ERDA Road, Makarpura Industrial Estate, Vadodara-390 010, India.

EPABX : +91 (0265) 2642942, 2642964, 2642377, 3043128 / 29 / 30 / 31 / 33

Fax : +91 (0265) 2638382

E-mail : erda@erda.org

Web : http://www.erda.org



TEST REPORT NO.: RP-1617-049429

DATE: 24/01/2017

SHEET 6 OF 34

Operating and test procedure of ports of sample under test as specified by the customer:

1) Power Supply:

'Non-operate' condition

- Apply 110VDC to Auxiliary power supply through CDN.
- During the test, apply $0.90 \cdot I_n$ current to each of the 3 Phase input and $0.9 \cdot I_n$ to 'Earth fault' input.

2) A, B & C PT Input:

'Non-operate' condition:

- Apply 110VDC to Auxiliary power supply.
- During the test, apply $0.90 \cdot I_n$ current to each of the 3 Phase input and $0.9 \cdot I_n$ to 'Earth fault' input.
- Apply 63.5 VAC to all PT input through CDN.

3) N PT Input:

'Non-operate' condition:

- Apply 110VDC to Auxiliary power supply.
- During the test, apply $0.90 \cdot I_n$ current to each of the 3 Phase input and $0.9 \cdot I_n$ to 'Earth fault' input.
- Apply 63.5 VAC to N PT input through CDN.

4) A, B & C CT Input:

'Non-operate' condition:

- Apply 110VDC to Auxiliary power supply.
- During the test, apply $0.90 \cdot I_n$ current to each of the CT input through CDN.
- During the test, apply $0.9 \cdot I_n$ current to Earth fault input.

PREPARED BY

T. Sheshe

CHECKED BY

Abhishek

TL 1424172





Certificate No. : T-3359

ELECTRICAL RESEARCH AND DEVELOPMENT ASSOCIATION

(Accredited by the National Accreditation Board for Testing and Calibration Laboratories, Govt. of India)

ERDA Road, Makarpura Industrial Estate, Vadodara-390 010, India.

EPABX : +91 (0265) 2642942, 2642964, 2642377, 3043128 / 29 / 30 / 31 / 33

Fax : +91 (0265) 2638382

E-mail : erda@erda.org

Web : http://www.erda.org



TEST REPORT NO.: RP-1617-049429

DATE: 24/01/2017

SHEET 7 OF 34

Operating and test procedure of ports of sample under test as specified by the customer:

Continued....

5) Earth fault Input:

'Non-operate' condition:

- Apply 110VDC to Auxiliary power supply.
- Apply $0.9 \cdot I_n$ current to 'Earth fault' input through CDN.
- During the test, apply $0.90 \cdot I_n$ current to 3 Phase current input.

6) Binary Input For H card (IN1):

'Non-Operate' condition:

- Apply 110VDC to Auxiliary power supply.
- Apply 10 VDC to Binary Input (IN1) through CDN.
- During the test apply $0.90 \cdot I_n$ current to 3 phase current input, $0.9 \cdot I_n$ to Earth fault input.

7) Binary Input For I card (IN1):

'Non-Operate' condition:

- Apply 110VDC to Auxiliary power supply.
- Apply 10 VDC to Binary Input (IN1) through CDN.
- During the test apply $0.90 \cdot I_n$ current to 3 phase current input, $0.9 \cdot I_n$ to Earth fault input.

PREPARED BY

CHECKED BY

T. Ghosh

Almit

TL 1424173





Certificate No. : T-3359

ELECTRICAL RESEARCH AND DEVELOPMENT ASSOCIATION

(Accredited by the National Accreditation Board for Testing and Calibration Laboratories, Govt. of India)

ERDA Road, Makarpura Industrial Estate, Vadodara-390 010, India.

EPABX : +91 (0265) 2642942, 2642964, 2642377, 3043128 / 29 / 30 / 31 / 33

Fax : +91 (0265) 2638382

E-mail : erda@erda.org

Web : http://www.erda.org



TEST REPORT NO.: RP-1617-049429

DATE: 24/01/2017

SHEET 8 OF 34

Annexure-II

Test shall be performed on the following ports:

Sr. No.	Port	Category	CDN	Condition	TEST LEVEL
1)	Power Supply	Aux. Supply	CDN	Non-operate	±4kV & 5 kHz
2)	A, B & C CT Input (1Amp./5Amp. CT)	Phase CT Input- A	CDN	Non-operate	±4kV & 5 kHz
		Phase CT Input- B	CDN	Non-operate	±4kV & 5 kHz
		Phase CT Input- C	CDN	Non-operate	±4kV & 5 kHz
3)	Earth Input (1Amp/5Amp. CT)	Earth CT Input	CDN	Non-operate	±4kV & 5 kHz
4)	A, B & C PT Input	Phase PT Input- A	CDN	Non-operate	±4kV & 5 kHz
		Phase PT Input- B	CDN	Non-operate	±4kV & 5 kHz
		Phase PT Input- C	CDN	Non-operate	±4kV & 5 kHz
5)	N PT Input	N PT Input	CDN	Non-operate	±4kV & 5 kHz
6)	Binary Input For H card (IN1)	Input Port	CDN	Non-operate	±4kV & 5 kHz
7)	Binary Input For I card (IN1)	Input Port	CDN	Non-operate	±4kV & 5 kHz

PREPARED BY

T. Shesha

CHECKED BY

[Signature]

TL 1424174





Certificate No. : T-3359

ELECTRICAL RESEARCH AND DEVELOPMENT ASSOCIATION

(Accredited by the National Accreditation Board for Testing and Calibration Laboratories, Govt. of India)

ERDA Road, Makarpura Industrial Estate, Vadodara-390 010, India.

EPABX : +91 (0265) 2642942, 2642964, 2642377, 3043128 / 29 / 30 / 31 / 33

Fax : +91 (0265) 2638382

E-mail : erda@erda.org

Web : <http://www.erda.org>



TEST REPORT NO.: RP-1617-049429

DATE: 24/01/2017

SHEET 9 OF 34

LIST OF THE MAJOR EQUIPMENTS USED DURING THE TEST

Sr. No	Details of equipments used	Specifications	Traceability
1)	Fast Transient Noise Simulator with Coupling Decoupling Network <ul style="list-style-type: none">ERDA Sr. No: 17010 & 17011Validity of calibration till date: 07/11/2017	250V to 4.00 kV $\pm 10\%$ in both polarities Rise time: 5ns $\pm 30\%$ Pulse Width: 50 ns $\pm 30\%$ Pulse Repeating Frequency: 5.0 kHz and 100 kHz.	Calibration results are traceable to National standard.
2)	Relay Test Unit (provided by customer) <ul style="list-style-type: none">Sr. No. 060803068Make: DobleValidity of calibration till date: 03.03.2017	AC Amplitude Accuracy at 50/60 Hz Voltage & Current Sources: Accuracy: Typically 0.02% of Rdg Timers and Triggers Accuracy: $\pm 0.0005\%$ of Rdg, $\pm 50\mu\text{sec}$.	Calibration results are traceable to National Standards
PREPARED BY <i>T. Shushko</i>		CHECKED BY <i>Deepak</i>	

TL 1424175





Certificate No. : T-3359

ELECTRICAL RESEARCH AND DEVELOPMENT ASSOCIATION

(Accredited by the National Accreditation Board for Testing and Calibration Laboratories, Govt. of India)

ERDA Road, Makarpura Industrial Estate, Vadodara-390 010, India.

EPABX : +91 (0265) 2642942, 2642964, 2642377, 3043128 / 29 / 30 / 31 / 33

Fax : +91 (0265) 2638382

E-mail : erda@erda.org


Web : http://www.erda.org



TEST REPORT NO.: RP-1617-049429

DATE: 24/01/2017

SHEET 10 OF 34



Test set up block diagram for Electrical fast transient/burst Immunity test

PREPARED BY

T. Shushk

CHECKED BY

[Signature]

TL 1424176





Certificate No. : T-3359

ELECTRICAL RESEARCH AND DEVELOPMENT ASSOCIATION

(Accredited by the National Accreditation Board for Testing and Calibration Laboratories, Govt. of India)

ERDA Road, Makarpura Industrial Estate, Vadodara-390 010, India.

EPABX : +91 (0265) 2642942, 2642964, 2642377, 3043128 / 29 / 30 / 31 / 33

Fax : +91 (0265) 2638382

E-mail : erda@erda.org

Web : http://www.erda.org



TEST REPORT NO.: RP-1617-049429 DATE: 24/01/2017 SHEET 11 OF 34

Sr. No.	Particular of test and Cl. No.	Requirement as per customer specifications	Obtained value	Remarks
	Electrical fast transient as per customer requirements & test procedure followed as per Cl. No.7.2.5 of IEC 60255-26: 2013	<p>The test procedure shall be followed as per clause 7.2.5 of IEC 60255-26: 2013 & IEC 61000-4-4: 2012.</p> <p>The test setup and procedure as per Table 13 of IEC 60255-26:2013.</p> <p>Test specification as per item 4.2 of table no.4 of IEC 60255-26:2013 for auxiliary power supply port are mentioned below.</p> <ul style="list-style-type: none"> • Rise time t_r / duration time t_d : 5/50 ns • Test Level ZONE A : 4 kV peak voltage • Repetition frequency: 5 kHz <p>Performance test shall be carried out on EUT before and after the Electrical fast transient test.</p> <p>Electrical fast transient shall be applied under 'non-operate' condition of EUT as specified by customer, with 110VDC.</p> <p>Performance test shall be carried out before the test and after the test. EUT should confirm and comply with claimed tolerance as mentioned above.</p>	<p>The EUT was energized & operated as specified on sheet no.3 & 4 of this report.</p> <p>110VDC was applied to Auxiliary power supply of the EUT through power supply.</p>	Conforms
PREPARED BY		CHECKED BY		
<i>T. Shreshth</i>		<i>[Signature]</i>		

TL 1424177





ELECTRICAL RESEARCH AND DEVELOPMENT ASSOCIATION

(Accredited by the National Accreditation Board for Testing and Calibration Laboratories, Govt. of India)

ERDA Road, Makarpura Industrial Estate, Vadodara-390 010, India.

EPABX : +91 (0265) 2642942, 2642964, 2642377, 3043128 / 29 / 30 / 31 / 33

Fax : +91 (0265) 2638382

E-mail : erda@erda.org

Web : http://www.erda.org



TEST REPORT NO.: RP-1617-049429

DATE: 24/01/2017

SHEET 12 OF 34

Sr. No	Particular of test and Cl. No.	Requirement as per customer specifications	Obtained value	Remarks
		1) Power Supply port: ('Non-operate' condition) Operating & test procedure of port & performance criteria as specified by customer mentioned on sheet no. 6 of this report.	1) 'Power Supply' port: ('Non-operate' condition) Performance test was carried out on 'Power Supply' port of EUT before & after test. The obtained values are mentioned in Annexure-III of this report. The performance of EUT was checked before, during and after the test. Observed parameters are mentioned on sheet no.13 of this report.	
PREPARED BY <i>T. Ghosh</i>		CHECKED BY <i>Alhit</i>		

TL 1424178





Certificate No. : T-3359

ELECTRICAL RESEARCH AND DEVELOPMENT ASSOCIATION

(Accredited by the National Accreditation Board for Testing and Calibration Laboratories, Govt. of India)

ERDA Road, Makarpura Industrial Estate, Vadodara-390 010, India.

EPABX : +91 (0265) 2642942, 2642964, 2642377, 3043128 / 29 / 30 / 31 / 33

Fax : +91 (0265) 2638382

E-mail : erda@erda.org

Web : http://www.erda.org



TEST REPORT NO.: RP-1617-049429

DATE: 24/01/2017

SHEET 13 OF 34

Observed parameters

Performance test was carried out on the 'Power supply' port of EUT in 'Non-operate' condition. Following parameters were checked before, during and after the test on EUT.

Function	Conditions for acceptance	As specified by customer
Protection	Normal performance within the specification limits, during and after the test	<ul style="list-style-type: none"> The relay remained stable during the test. No false indication was observed on EUT before, during and after the test.
Command and control	Normal performance within the specification limits, during and after the test	'Non-operate' condition: <ul style="list-style-type: none"> Before, during and after the test, assigned general pick up contact output 3 did not operate, which was checked through trip LED. (i.e. LED was OFF)
Measurement	Temporary degradation during the test, with self-recovery at the end of the test. No loss of store data.	<ul style="list-style-type: none"> The operating value was within 1 to 1.1 times of set pickup value before & after the test. The trip time value was within $\pm 12.5\%$ of actual value. (Actual time 10.029 Sec.) before & after the test.
Integral human-machine interface and visual alarms	Temporary degradation or loss of function during the test, with self-recovery at the end of the test. No loss of store data.	'Non operate' condition : <ul style="list-style-type: none"> ENABLED LED was continuously 'ON' & all other LEDs was remained 'OFF' before, during and after the test.
Data communication ^b	Possible bit error rate increase but no loss of transmitted data.	Not applicable
Binary input, binary output and output contacts	No unwanted change of status is allowed during the test ^a .	'Non-operate' condition: <ul style="list-style-type: none"> Before, during and after the test, assigned general pick up contact output 3 did not operate, which was checked through trip LED. (i.e. LED was OFF)

a For binary input the manufacture shall state the minimum filtering value for which the test was successful.

b Excluding communication ports for protection or control functionality. For those acceptance criteria see protection or command and control.

PREPARED BY

CHECKED BY

T. Shukla

C. D. D. D.

TL 1424451





Certificate No. : T-3359

ELECTRICAL RESEARCH AND DEVELOPMENT ASSOCIATION

(Accredited by the National Accreditation Board for Testing and Calibration Laboratories, Govt. of India)

ERDA Road, Makarpura Industrial Estate, Vadodara-390 010, India.

EPABX : +91 (0265) 2642942, 2642964, 2642377, 3043128 / 29 / 30 / 31 / 33

Fax : +91 (0265) 2638382

E-mail : erda@erda.org

Web : http://www.erda.org



TEST REPORT NO.: RP-1617-049429

DATE: 24/01/2017

SHEET 14 OF 34

Annexure-III Obtained values

Before Test:

	A Ph. Value	B Ph. Value	C Ph. Value	Earth	Tolerance
Pick Up	1.05 A	1.05 A	1.06 A	1.06 A	1-1.1 Amp
Operating Time (2 Amp)	10.06 sec	10.07 sec	10.09 sec	10.07 sec	8.77-11.29 Sec

After Test:

	A Ph. Value	B Ph. Value	C Ph. Value	Earth	Tolerance
Pick Up	1.05 A	1.05 A	1.06 A	1.05 A	1-1.1 Amp
Operating Time (2 Amp)	10.52 sec	10.07 sec	10.09 sec	10.07 sec	8.77-11.29 Sec

Note: During performance test of sample, measured values were observed on Relay test unit (Doble)/Laptop.

PREPARED BY

CHECKED BY

T. K. Desai

[Signature]

TL 1424180





Certificate No. : T-3359

ELECTRICAL RESEARCH AND DEVELOPMENT ASSOCIATION

(Accredited by the National Accreditation Board for Testing and Calibration Laboratories, Govt. of India)

ERDA Road, Makarpura Industrial Estate, Vadodara-390 010, India.

EPABX : +91 (0265) 2642942, 2642964, 2642377, 3043128 / 29 / 30 / 31 / 33

Fax : +91 (0265) 2638382

E-mail : erda@erda.org

Web : http://www.erda.org



TEST REPORT NO.: RP-1617-049429

DATE: 24/01/2017

SHEET 15 OF 34

Sr. No	Particular of test and Cl. No.	Requirement as per customer specifications	Obtained value	Remarks
		<p>2) A, B & C PT Input: ('Non operate' condition)</p> <p>EUT in under 'non-operate' condition, using CDN as per operating procedure mentioned on Sheets No. 6 of this report.</p> <p>Test specification as per item 6.2 of table no.6 of IEC 60255-26:2013 for Input and output ports are mentioned below.</p> <ul style="list-style-type: none"> • Rise time t_r / duration time t_d : 5/50 ns • Test Level ZONE A : 4 kV peak voltage • Repetition frequency: 5 kHz <p>Operating & test procedure of port & performance criteria as specified by customer mentioned on sheet no. 6 of this report.</p>	<p>2) A, B & C PT Input: ('Non operate' condition)</p> <p>Performance test was carried out on A, B & C PT Input port of EUT before & after the test. The obtained values are mentioned in Annexure-IV.</p> <p>The performance of EUT was checked before, during and after the test. Observed parameters are mentioned on sheet no. 16 of this report.</p>	
<p>PREPARED BY</p> <p><i>T. Shrestha</i></p>		<p>CHECKED BY</p> <p><i>[Signature]</i></p>		

TL 1424181





Certificate No. : T-3359

ELECTRICAL RESEARCH AND DEVELOPMENT ASSOCIATION

(Accredited by the National Accreditation Board for Testing and Calibration Laboratories, Govt. of India)

ERDA Road, Makarpura Industrial Estate, Vadodara-390 010, India.

EPABX : +91 (0265) 2642942, 2642964, 2642377, 3043128 / 29 / 30 / 31 / 33

Fax : +91 (0265) 2638382

E-mail : erda@erda.org

Web : http://www.erda.org



TEST REPORT NO.: RP-1617-049429

DATE: 24/01/2017

SHEET 16 OF 34

Observed parameters

Performance test was carried out on the 'A, B & C PT Input' port of EUT in 'Non-operate' condition. Following monitoring parameters were checked before, during and after the test on EUT.

Function	Conditions for acceptance	As specified by customer
Protection	Normal performance within the specification limits, during and after the test	<ul style="list-style-type: none"> The relay remained stable during the test. No false indication was observed on EUT before, during and after the test.
Command and control	Normal performance within the specification limits, during and after the test	'Non-operate' condition: <ul style="list-style-type: none"> Before, during and after the test, assigned general pick up contact output 3 did not operate, which was checked through trip LED. (i.e. LED was OFF)
Measurement	Temporary degradation during the test, with self-recovery at the end of the test. No loss of store data.	<ul style="list-style-type: none"> The operating value was within 1 to 1.1 times of set pickup value before & after the test. The trip time value was within $\pm 12.5\%$ of actual value. (Actual time 10.029 Sec.) before & after the test.
Integral human-machine interface and visual alarms	Temporary degradation or loss of function during the test, with self-recovery at the end of the test. No loss of store data.	'Non operate' condition : <ul style="list-style-type: none"> ENABLED LED was continuously 'ON' & all other LEDs was remained 'OFF' before, during and after the test.
Data communication ^b	Possible bit error rate increase but no loss of transmitted data.	Not applicable
Binary input, binary output and output contacts	No unwanted change of status is allowed during the test ^a .	'Non-operate' condition: <ul style="list-style-type: none"> Before, during and after the test, assigned general pick up contact output 3 did not operate, which was checked through trip LED. (i.e. LED was OFF)

a For binary input the manufacture shall state the minimum filtering value for which the test was successful.

b Excluding communication ports for protection or control functionality. For those acceptance criteria see protection or command and control.

PREPARED BY

T. K. Shrivastava

CHECKED BY

[Signature]

TL 1424452





Certificate No. : T-3359

ELECTRICAL RESEARCH AND DEVELOPMENT ASSOCIATION

(Accredited by the National Accreditation Board for Testing and Calibration Laboratories, Govt. of India)

ERDA Road, Makarpura Industrial Estate, Vadodara-390 010, India.

EPABX : +91 (0265) 2642942, 2642964, 2642377, 3043128 / 29 / 30 / 31 / 33

Fax : +91 (0265) 2638382

E-mail : erda@erda.org

Web : <http://www.erda.org>



TEST REPORT NO.: RP-1617-049429

DATE: 24/01/2017

SHEET 17 OF 34

Annexure-IV Obtained values

Before Test:

	A Ph. Value	B Ph. Value	C Ph. Value	Earth	Tolerance
Pick Up	1.05 A	1.05 A	1.06 A	1.05 A	1-1.1 Amp
Operating Time (2 Amp)	9.95 sec	10.06 sec	10.09 sec	10.07 sec	8.77-11.29 Sec

After Test:

	A Ph. Value	B Ph. Value	C Ph. Value	Earth	Tolerance
Pick Up	1.05 A	1.05 A	1.06 A	1.05 A	1-1.1 Amp
Operating Time (2 Amp)	10.06 sec	10.06 sec	9.96 sec	10.06 sec	8.77-11.29 Sec

Note: During performance test of sample, measured values were observed on Relay test unit (Doble)/Laptop.

PREPARED BY

CHECKED BY

T. J. Kulkarni

[Signature]

TL 1424183





Certificate No. : T-3359

ELECTRICAL RESEARCH AND DEVELOPMENT ASSOCIATION

(Accredited by the National Accreditation Board for Testing and Calibration Laboratories, Govt. of India)

ERDA Road, Makarpura Industrial Estate, Vadodara-390 010, India.

EPABX : +91 (0265) 2642942, 2642964, 2642377, 3043128 / 29 / 30 / 31 / 33

Fax : +91 (0265) 2638382

E-mail : erda@erda.org

Web : http://www.erda.org



TEST REPORT NO.: RP-1617-049429

DATE: 24/01/2017

SHEET 18 OF 34

Sr. No	Particular of test and Cl. No.	Requirement as per customer specifications	Obtained value	Remarks
		<p>3) N PT Input port: ('Non operate' condition)</p> <p>EUT in under 'non-operate' condition, using CDN as per operating procedure mentioned on Sheets No. 6 of this report.</p> <p>Test specification as per item 6.2 of table no.6 of IEC 60255-26:2013 for Input and output ports are mentioned below.</p> <ul style="list-style-type: none"> • Rise time t_r / duration time t_d: 5/50 ns • Test Level ZONE A : 4 kV peak voltage • Repetition frequency: 5 kHz <p>Operating & test procedure of port & performance criteria as specified by customer mentioned on sheet no. 6 of this report.</p>	<p>3) N PT Input port: ('Non operate' condition)</p> <p>Performance test was carried out on N PT Input port of EUT before & after the test. The obtained values are mentioned in Annexure-V respectively.</p> <p>The performance of EUT was checked before, during and after the test. Observed parameters are mentioned on sheet no. 19 of this report</p>	
PREPARED BY		CHECKED BY		
<i>T. B. Mesh</i>		<i>Mesh</i>		

TL 1424184





Certificate No. : T-3359

ELECTRICAL RESEARCH AND DEVELOPMENT ASSOCIATION

(Accredited by the National Accreditation Board for Testing and Calibration Laboratories, Govt. of India)

ERDA Road, Makarpura Industrial Estate, Vadodara-390 010, India.

EPABX : +91 (0265) 2642942, 2642964, 2642377, 3043128 / 29 / 30 / 31 / 33

Fax : +91 (0265) 2638382

E-mail : erda@erda.org

Web : http://www.erda.org



TEST REPORT NO.: RP-1617-049429

DATE: 24/01/2017

SHEET 19 OF 34

Observed parameters

Performance test was carried out on the 'N PT Input' port of EUT in 'Non-operate' & 'Operate' condition. Following monitoring parameters were checked before, during and after the test on EUT.

Function	Conditions for acceptance	As specified by customer
Protection	Normal performance within the specification limits, during and after the test	<ul style="list-style-type: none"> The relay remained stable during the test. No false indication was observed on EUT before, during and after the test.
Command and control	Normal performance within the specification limits, during and after the test	'Non-operate' condition: <ul style="list-style-type: none"> Before, during and after the test, assigned general pick up contact output 3 did not operate, which was checked through trip LED. (i.e. LED was OFF)
Measurement	Temporary degradation during the test, with self-recovery at the end of the test. No loss of store data.	<ul style="list-style-type: none"> The operating value was within 1 to 1.1 times of set pickup value before & after the test. The trip time value was within $\pm 12.5\%$ of actual value. (Actual time 10.029 Sec.) before & after the test.
Integral human-machine interface and visual alarms	Temporary degradation or loss of function during the test, with self-recovery at the end of the test. No loss of store data.	'Non operate' condition : <ul style="list-style-type: none"> ENABLED LED was continuously 'ON' & all other LEDs was remained 'OFF' before, during and after the test.
Data communication ^b	Possible bit error rate increase but no loss of transmitted data.	Not applicable
Binary input, binary output and output contacts	No unwanted change of status is allowed during the test ^a .	'Non-operate' condition: <ul style="list-style-type: none"> Before, during and after the test, assigned general pick up contact output 3 did not operate, which was checked through trip LED. (i.e. LED was OFF)

a For binary input the manufacture shall state the minimum filtering value for which the test was successful.

b Excluding communication ports for protection or control functionality. For those acceptance criteria see protection or command and control.

PREPARED BY

T. Shrestha

CHECKED BY

[Signature]

TL 1424453





Certificate No. : T-3359

ELECTRICAL RESEARCH AND DEVELOPMENT ASSOCIATION

(Accredited by the National Accreditation Board for Testing and Calibration Laboratories, Govt. of India)

ERDA Road, Makarpura Industrial Estate, Vadodara-390 010, India.

EPABX : +91 (0265) 2642942, 2642964, 2642377, 3043128 / 29 / 30 / 31 / 33

Fax : +91 (0265) 2638382

E-mail : erda@erda.org

Web : http://www.erda.org



TEST REPORT NO.: RP-1617-049429

DATE: 24/01/2017

SHEET 20 OF 34

Annexure-V Obtained values

Before Test:

	A Ph. Value	B Ph. Value	C Ph. Value	Earth	Tolerance
Pick Up	1.05 A	1.05 A	1.06 A	1.05 A	1-1.1 Amp
Operating Time (2 Amp)	9.95 sec	10.06 sec	10.09 sec	10.07 sec	8.77-11.29 Sec

After Test:

	A Ph. Value	B Ph. Value	C Ph. Value	Earth	Tolerance
Pick Up	1.05 A	1.05 A	1.06 A	1.06 A	1-1.1 Amp
Operating Time (2 Amp)	10.76 sec	10.07 sec	10.08 sec	10.00 sec	8.77-11.29 Sec

Note: During performance test of sample, measured values were observed on Relay test unit (Doble)/Laptop.

PREPARED BY

CHECKED BY

T. Bhuske

[Signature]

TL 1424186





Certificate No. : T-3359

ELECTRICAL RESEARCH AND DEVELOPMENT ASSOCIATION

(Accredited by the National Accreditation Board for Testing and Calibration Laboratories, Govt. of India)

ERDA Road, Makarpura Industrial Estate, Vadodara-390 010, India.

EPABX : +91 (0265) 2642942, 2642964, 2642377, 3043128 / 29 / 30 / 31 / 33

Fax : +91 (0265) 2638382

E-mail : erda@erda.org

Web : http://www.erda.org



TEST REPORT NO.: RP-1617-049429

DATE: 24/01/2017

SHEET 21 OF 34

Sr. No	Particular of test and Cl. No.	Requirement as per customer specifications	Obtained value	Remarks
		<p>4) A, B & C CT input port: ('Non operate' condition)</p> <p>EUT in under 'non-operate' & 'operate' condition, using Capacitive Clamp as per operating procedure mentioned on Sheets No. 6 of this report.</p> <p>Test specification as per item 6.2 of table no.6 of IEC 60255-26:2013 for Input and output ports are mentioned below.</p> <ul style="list-style-type: none"> • Rise time t_r / duration time t_d : 5/50 ns • Test Level ZONE A : 4 kV peak voltage • Repetition frequency: 5 kHz <p>Operating & test procedure of port & performance criteria as specified by customer mentioned Sheets No. 6 of this report.</p>	<p>4) A, B & C CT port: ('Non operate' condition)</p> <p>Performance test was carried out on A, B & C CT input port of EUT before & after the test. The obtained values are mentioned in Annexure-VI.</p> <p>The performance of EUT was checked before, during and after the test. Observed parameters are mentioned on sheet no. 22 of this report.</p>	
PREPARED BY <i>T. G. Shah</i>		CHECKED BY <i>[Signature]</i>		

TL 1424187





Certificate No. : T-3359

ELECTRICAL RESEARCH AND DEVELOPMENT ASSOCIATION

(Accredited by the National Accreditation Board for Testing and Calibration Laboratories, Govt. of India)

ERDA Road, Makarpura Industrial Estate, Vadodara-390 010, India.

EPABX : +91 (0265) 2642942, 2642964, 2642377, 3043128 / 29 / 30 / 31 / 33

Fax : +91 (0265) 2638382

E-mail : erda@erda.org

Web : http://www.erda.org



TEST REPORT NO.: RP-1617-049429

DATE: 24/01/2017

SHEET 22 OF 34

Observed parameters

Performance test was carried out on the 'A, B & C CT input port' of EUT in 'Non-operate' & 'Operate' condition. Following monitoring parameters were checked before, during and after the test on EUT.

Function	Conditions for acceptance	As specified by customer
Protection	Normal performance within the specification limits, during and after the test	<ul style="list-style-type: none"> The relay remained stable during the test. No false indication was observed on EUT before, during and after the test.
Command and control	Normal performance within the specification limits, during and after the test	'Non-operate' condition: <ul style="list-style-type: none"> Before, during and after the test, assigned general pick up contact output 3 did not operate, which was checked through trip LED. (i.e. LED was OFF)
Measurement	Temporary degradation during the test, with self-recovery at the end of the test. No loss of store data.	<ul style="list-style-type: none"> The operating value was within 1 to 1.1 times of set pickup value before & after the test. The trip time value was within $\pm 12.5\%$ of actual value. (Actual time 10.029 Sec.) before & after the test.
Integral human-machine interface and visual alarms	Temporary degradation or loss of function during the test, with self-recovery at the end of the test. No loss of store data.	'Non operate' condition : <ul style="list-style-type: none"> ENABLED LED was continuously 'ON' & all other LEDs was remained 'OFF' before, during and after the test.
Data communication ^b	Possible bit error rate increase but no loss of transmitted data.	Not applicable
Binary input, binary output and output contacts	No unwanted change of status is allowed during the test ^a .	'Non-operate' condition: <ul style="list-style-type: none"> Before, during and after the test, assigned general pick up contact output 3 did not operate, which was checked through trip LED. (i.e. LED was OFF)

a For binary input the manufacture shall state the minimum filtering value for which the test was successful.

b Excluding communication ports for protection or control functionality. For those acceptance criteria see protection or command and control.

PREPARED BY

T. Shusha

CHECKED BY

Atul

TL 1424454





Certificate No. : T-3359

ELECTRICAL RESEARCH AND DEVELOPMENT ASSOCIATION

(Accredited by the National Accreditation Board for Testing and Calibration Laboratories, Govt. of India)

ERDA Road, Makarpura Industrial Estate, Vadodara-390 010, India.

EPABX : +91 (0265) 2642942, 2642964, 2642377, 3043128 / 29 / 30 / 31 / 33

Fax : +91 (0265) 2638382

E-mail : erda@erda.org

Web : http://www.erda.org



TEST REPORT NO.: RP-1617-049429

DATE: 24/01/2017

SHEET 23 OF 34

Annexure-VI Obtained values

Before Test:

	A Ph. Value	B Ph. Value	C Ph. Value	Earth	Tolerance
Pick Up	1.05 A	1.05 A	1.06 A	1.06 A	1-1.1 Amp
Operating Time (2 Amp)	10.76 sec	10.07 sec	10.08 sec	10.00 sec	8.77-11.29 Sec

After Test:

	A Ph. Value	B Ph. Value	C Ph. Value	Earth	Tolerance
Pick Up	1.05 A	1.05 A	1.06 A	1.05 A	1-1.1 Amp
Operating Time (2 Amp)	10.65 sec	10.06 sec	10.09 sec	10.06 sec	8.77-11.29 Sec

Note: During performance test of sample, measured values were observed on Relay test unit (Doble)/Laptop.

PREPARED BY

CHECKED BY

T. Shukla

[Signature]

TL 1424189





Certificate No. : T-3359

ELECTRICAL RESEARCH AND DEVELOPMENT ASSOCIATION

(Accredited by the National Accreditation Board for Testing and Calibration Laboratories, Govt. of India)

ERDA Road, Makarpura Industrial Estate, Vadodara-390 010, India.

EPABX : +91 (0265) 2642942, 2642964, 2642377, 3043128 / 29 / 30 / 31 / 33

Fax : +91 (0265) 2638382

E-mail : erda@erda.org

Web : http://www.erda.org



TEST REPORT NO.: RP-1617-049429

DATE: 24/01/2017

SHEET 24 OF 34

Sr. No	Particular of test and Cl. No.	Requirement as per customer specifications	Obtained value	Remarks
		<p>5) Earth fault input port: ('Non operate' condition)</p> <p>EUT in under 'non-operate' condition, using CDN as per operating procedure mentioned on Sheets No. 7 of this report.</p> <p>Test specification as per item 6.2 of table no.6 of IEC 60255-26:2013 for Input and output ports are mentioned below.</p> <ul style="list-style-type: none"> • Rise time t_r / duration time t_d : 5/50 ns • Test Level ZONE A : 4 kV peak voltage • Repetition frequency: 5 kHz <p>Operating & test procedure of port & performance criteria as specified by customer mentioned Sheets No. 7 of this report.</p>	<p>5) Earth fault input port: ('Non operate' condition)</p> <p>Performance test was carried out on 'Earth fault input port of EUT before & after the test. The obtained values are mentioned in Annexure-VII</p> <p>The performance of EUT was checked before, during and after the test. Observed parameters are mentioned on sheet no. 25 of this report.</p>	
<p>PREPARED BY <i>T. J. Kumbhar</i></p>		<p>CHECKED BY <i>[Signature]</i></p>		

TL 1424190





Certificate No. : T-3359

ELECTRICAL RESEARCH AND DEVELOPMENT ASSOCIATION

(Accredited by the National Accreditation Board for Testing and Calibration Laboratories, Govt. of India)

ERDA Road, Makarpura Industrial Estate, Vadodara-390 010, India.

EPABX : +91 (0265) 2642942, 2642964, 2642377, 3043128 / 29 / 30 / 31 / 33

Fax : +91 (0265) 2638382

E-mail : erda@erda.org

Web : http://www.erda.org



TEST REPORT NO.: RP-1617-049429

DATE: 24/01/2017

SHEET 25 OF 34

Observed parameters

Performance test was carried out on the 'Earth fault input port of EUT in 'Non-operate' condition. Following monitoring parameters were checked before, during and after the test on EUT.

Function	Conditions for acceptance	As specified by customer
Protection	Normal performance within the specification limits, during and after the test	<ul style="list-style-type: none"> The relay remained stable during the test. No false indication was observed on EUT before, during and after the test.
Command and control	Normal performance within the specification limits, during and after the test	'Non-operate' condition: <ul style="list-style-type: none"> Before, during and after the test, assigned general pick up contact output 3 did not operate, which was checked through trip LED. (i.e. LED was OFF)
Measurement	Temporary degradation during the test, with self-recovery at the end of the test. No loss of store data.	<ul style="list-style-type: none"> The operating value was within 1 to 1.1 times of set pickup value before & after the test. The trip time value was within $\pm 12.5\%$ of actual value. (Actual time 10.029 Sec.) before & after the test.
Integral human-machine interface and visual alarms	Temporary degradation or loss of function during the test, with self-recovery at the end of the test. No loss of store data.	'Non operate' condition : <ul style="list-style-type: none"> ENABLED LED was continuously 'ON' & all other LEDs was remained 'OFF' before, during and after the test.
Data communication ^b	Possible bit error rate increase but no loss of transmitted data.	Not applicable
Binary input, binary output and output contacts	No unwanted change of status is allowed during the test ^a .	'Non-operate' condition: <ul style="list-style-type: none"> Before, during and after the test, assigned general pick up contact output 3 did not operate, which was checked through trip LED. (i.e. LED was OFF)

a For binary input the manufacture shall state the minimum filtering value for which the test was successful.

b Excluding communication ports for protection or control functionality. For those acceptance criteria see protection or command and control.

PREPARED BY

T. Shukla

CHECKED BY

[Signature]

TL 1424455





Certificate No. : T-3359

ELECTRICAL RESEARCH AND DEVELOPMENT ASSOCIATION

(Accredited by the National Accreditation Board for Testing and Calibration Laboratories, Govt. of India)

ERDA Road, Makarpura Industrial Estate, Vadodara-390 010, India.

EPABX : +91 (0265) 2642942, 2642964, 2642377, 3043128 / 29 / 30 / 31 / 33

Fax : +91 (0265) 2638382

E-mail : erda@erda.org

Web : http://www.erda.org



TEST REPORT NO.: RP-1617-049429

DATE: 24/01/2017

SHEET 26 OF 34

Annexure-VII Obtained values

Before Test:

	A Ph. Value	B Ph. Value	C Ph. Value	Earth	Tolerance
Pick Up	1.05 A	1.06 A	1.05 A	1.05 A	1-1.1 Amp
Operating Time (2 Amp)	10.81 sec	10.09 sec	10.01 sec	10.72 sec	8.77-11.29 Sec

After Test:

	A Ph. Value	B Ph. Value	C Ph. Value	Earth	Tolerance
Pick Up	1.05 A	1.06 A	1.05 A	1.06 A	1-1.1 Amp
Operating Time (2 Amp)	10.71 sec	10.60 sec	10.82 sec	10.06 sec	8.77-11.29 Sec

Note: During performance test of sample, measured values were observed on Relay test unit (Doble)/Laptop.

PREPARED BY

CHECKED BY

T. Ghush

R. K. K.

TL 1424192





Certificate No. : T-3359

ELECTRICAL RESEARCH AND DEVELOPMENT ASSOCIATION

(Accredited by the National Accreditation Board for Testing and Calibration Laboratories, Govt. of India)

ERDA Road, Makarpura Industrial Estate, Vadodara-390 010, India.

EPABX : +91 (0265) 2642942, 2642964, 2642377, 3043128 / 29 / 30 / 31 / 33

Fax : +91 (0265) 2638382

E-mail : erda@erda.org

Web : http://www.erda.org



TEST REPORT NO.: RP-1617-049429

DATE: 24/01/2017

SHEET 27 OF 34

Sr. No	Particular of test and Cl. No.	Requirement as per customer specifications	Obtained value	Remarks
		<p>6) Binary input port for H card (IN1): ('Non operate' condition)</p> <p>EUT in under 'non-operate' condition, using CDN as per operating procedure mentioned on Sheets No. 7 of this report.</p> <p>Test specification as per item 6.2 of table no.6 of IEC 60255-26:2013 for Input and output ports are mentioned below.</p> <ul style="list-style-type: none"> ◦ Rise time t_r / duration time t_d : 5/50 ns ◦ Test Level ZONE A : 4 kV peak voltage ◦ Repetition frequency: 5 kHz <p>Operating & test procedure of port & performance criteria as specified by customer mentioned Sheets No. 7 of this report.</p>	<p>6) Binary input port for H card (IN1) port: ('Non operate' condition)</p> <p>Performance test was carried out on 'Binary input port for H card (IN1) port of EUT before & after the test. The obtained values are mentioned in Annexure-VIII</p> <p>The performance of EUT was checked before, during and after the test. Observed parameters are mentioned on sheet no. 28 of this report.</p>	
<p>PREPARED BY <i>T. Ghos</i></p>		<p>CHECKED BY <i>Alkhi</i></p>		

TL 1424193





Certificate No. : T-3359

ELECTRICAL RESEARCH AND DEVELOPMENT ASSOCIATION

(Accredited by the National Accreditation Board for Testing and Calibration Laboratories, Govt. of India)

ERDA Road, Makarpura Industrial Estate, Vadodara-390 010, India.

EPABX : +91 (0265) 2642942, 2642964, 2642377, 3043128 / 29 / 30 / 31 / 33

Fax : +91 (0265) 2638382

E-mail : erda@erda.org

Web : http://www.erda.org



TEST REPORT NO.: RP-1617-049429

DATE: 24/01/2017

SHEET 28 OF 34

Observed parameters

Performance test was carried out on the 'Binary input port for H card (IN1) port of EUT in 'Non-operate' condition. Following monitoring parameters were checked before, during and after the test on EUT.

Function	Conditions for acceptance	As specified by customer
Protection	Normal performance within the specification limits, during and after the test	<ul style="list-style-type: none"> The relay remained stable during the test. No false indication was observed on EUT before, during and after the test.
Command and control	Normal performance within the specification limits, during and after the test	'Non-operate' condition: <ul style="list-style-type: none"> Before, during and after the test, assigned general pick up contact output 3 did not operate, which was checked through trip LED. (i.e. LED was OFF)
Measurement	Temporary degradation during the test, with self-recovery at the end of the test. No loss of store data.	<ul style="list-style-type: none"> The operating value was within 1 to 1.1 times of set pickup value before & after the test. The trip time value was within $\pm 12.5\%$ of actual value. (Actual time 10.029 Sec.) before & after the test.
Integral human-machine interface and visual alarms	Temporary degradation or loss of function during the test, with self-recovery at the end of the test. No loss of store data.	'Non operate' condition : <ul style="list-style-type: none"> ENABLED LED was continuously 'ON' & all other LEDs was remained 'OFF' before, during and after the test.
Data communication ^b	Possible bit error rate increase but no loss of transmitted data.	Not applicable
Binary input, binary output and output contacts	No unwanted change of status is allowed during the test ^a .	'Non-operate' condition: <ul style="list-style-type: none"> Before, during and after the test, assigned general pick up contact output 3 did not operate, which was checked through trip LED. (i.e. LED was OFF)

a For binary input the manufacture shall state the minimum filtering value for which the test was successful.
b Excluding communication ports for protection or control functionality. For those acceptance criteria see protection or command and control.

PREPARED BY

T. Shreshth

CHECKED BY

[Signature]

TL 1424456





Certificate No. : T-3359

ELECTRICAL RESEARCH AND DEVELOPMENT ASSOCIATION

(Accredited by the National Accreditation Board for Testing and Calibration Laboratories, Govt. of India)

ERDA Road, Makarpura Industrial Estate, Vadodara-390 010, India.

EPABX : +91 (0265) 2642942, 2642964, 2642377, 3043128 / 29 / 30 / 31 / 33

Fax : +91 (0265) 2638382

E-mail : erda@erda.org

Web : http://www.erda.org



TEST REPORT NO.: RP-1617-049429

DATE: 24/01/2017

SHEET 29 OF 34

Annexure-VIII Obtained values

Before Test:

	A Ph. Value	B Ph. Value	C Ph. Value	Earth	Tolerance
Pick Up	1.05 A	1.06 A	1.05 A	1.06 A	1-1.1 Amp
Operating Time (2 Amp)	10.71 sec	10.60 sec	10.82 sec	10.06 sec	8.77-11.29 Sec

After Test:

	A Ph. Value	B Ph. Value	C Ph. Value	Earth	Tolerance
Pick Up	1.05 A	1.06 A	1.06 A	1.06 A	1-1.1 Amp
Operating Time (2 Amp)	10.07 sec	10.07 sec	10.09 sec	10.08 sec	8.77-11.29 Sec

Note: During performance test of sample, measured values were observed on Relay test unit (Doble)/Laptop.

PREPARED BY

CHECKED BY

[Signature]

[Signature]

TL 1424195





Certificate No. : T-3359

ELECTRICAL RESEARCH AND DEVELOPMENT ASSOCIATION

(Accredited by the National Accreditation Board for Testing and Calibration Laboratories, Govt. of India)

ERDA Road, Makarpura Industrial Estate, Vadodara-390 010, India.

EPABX : +91 (0265) 2642942, 2642964, 2642377, 3043128 / 29 / 30 / 31 / 33

Fax : +91 (0265) 2638382

E-mail : erda@erda.org

Web : http://www.erda.org



TEST REPORT NO.: RP-1617-049429

DATE: 24/01/2017

SHEET 30 OF 34

Sr. No	Particular of test and Cl. No.	Requirement as per customer specifications	Obtained value	Remarks
		<p>7) Binary input port for I card (IN1): ('Non operate' condition)</p> <p>EUT in under 'non-operate' condition, using CDN as per operating procedure mentioned on Sheets No. 7 of this report.</p> <p>Test specification as per item 6.2 of table no.6 of IEC 60255-26:2013 for Input and output ports are mentioned below.</p> <ul style="list-style-type: none"> ◦ Rise time t_r / duration time t_d : 5/50 ns ◦ Test Level ZONE A : 4 kV peak voltage ◦ Repetition frequency: 5 kHz <p>Operating & test procedure of port & performance criteria as specified by customer mentioned Sheets No. 7 of this report.</p>	<p>7) Binary input port for I card (IN1) port: ('Non operate' condition)</p> <p>Performance test was carried out on 'Binary input port for I card (IN1) port of EUT before & after the test. The obtained values are mentioned in Annexure-IX</p> <p>The performance of EUT was checked before, during and after the test. Observed parameters are mentioned on sheet no. 31 of this report.</p>	
PREPARED BY <i>T. Shusho</i>		CHECKED BY <i>[Signature]</i>		

TL 1424457





Certificate No. : T-3359

ELECTRICAL RESEARCH AND DEVELOPMENT ASSOCIATION

(Accredited by the National Accreditation Board for Testing and Calibration Laboratories, Govt. of India)

ERDA Road, Makarpura Industrial Estate, Vadodara-390 010, India.

EPABX : +91 (0265) 2642942, 2642964, 2642377, 3043128 / 29 / 30 / 31 / 33

Fax : +91 (0265) 2638382

E-mail : erda@erda.org

Web : http://www.erda.org



TEST REPORT NO.: RP-1617-049429

DATE: 24/01/2017

SHEET 31 OF 34

Observed parameters

Performance test was carried out on the 'Binary input port for I card (IN1) port of EUT in 'Non-operate' condition. Following monitoring parameters were checked before, during and after the test on EUT.

Function	Conditions for acceptance	As specified by customer
Protection	Normal performance within the specification limits, during and after the test	<ul style="list-style-type: none"> The relay remained stable during the test. No false indication was observed on EUT before, during and after the test.
Command and control	Normal performance within the specification limits, during and after the test	'Non-operate' condition: <ul style="list-style-type: none"> Before, during and after the test, assigned general pick up contact output 3 did not operate, which was checked through trip LED. (i.e. LED was OFF)
Measurement	Temporary degradation during the test, with self-recovery at the end of the test. No loss of store data.	<ul style="list-style-type: none"> The operating value was within 1 to 1.1 times of set pickup value before & after the test. The trip time value was within $\pm 12.5\%$ of actual value. (Actual time 10.029 Sec.) before & after the test.
Integral human-machine interface and visual alarms	Temporary degradation or loss of function during the test, with self-recovery at the end of the test. No loss of store data.	'Non operate' condition : <ul style="list-style-type: none"> ENABLED LED was continuously 'ON' & all other LEDs was remained 'OFF' before, during and after the test.
Data communication ^b	Possible bit error rate increase but no loss of transmitted data.	Not applicable
Binary input, binary output and output contacts	No unwanted change of status is allowed during the test ^a .	'Non-operate' condition: <ul style="list-style-type: none"> Before, during and after the test, assigned general pick up contact output 3 did not operate, which was checked through trip LED. (i.e. LED was OFF)

a For binary input the manufacture shall state the minimum filtering value for which the test was successful.

b Excluding communication ports for protection or control functionality. For those acceptance criteria see protection or command and control.

PREPARED BY

T. Shrestha

CHECKED BY

M. K. Mittal

TL 1424458





Certificate No. : T-3359

ELECTRICAL RESEARCH AND DEVELOPMENT ASSOCIATION

(Accredited by the National Accreditation Board for Testing and Calibration Laboratories, Govt. of India)

ERDA Road, Makarpura Industrial Estate, Vadodara-390 010, India.

EPABX : +91 (0265) 2642942, 2642964, 2642377, 3043128 / 29 / 30 / 31 / 33

Fax : +91 (0265) 2638382

E-mail : erda@erda.org

Web : http://www.erda.org



TEST REPORT NO.: RP-1617-049429

DATE: 24/01/2017

SHEET 32 OF 34

Annexure-IX Obtained values

Before Test:

	A Ph. Value	B Ph. Value	C Ph. Value	Earth	Tolerance
Pick Up	1.05 A	1.06 A	1.06 A	1.06 A	1-1.1 Amp
Operating Time (2 Amp)	10.07 sec	10.07 sec	10.09 sec	10.08 sec	8.77-11.29 Sec

After Test:

	A Ph. Value	B Ph. Value	C Ph. Value	Earth	Tolerance
Pick Up	1.05 A	1.05 A	1.06 A	1.05 A	1-1.1 Amp
Operating Time (2 Amp)	10.64 sec	10.49 sec	10.09 sec	10.06 sec	8.77-11.29 Sec

Note: During performance test of sample, measured values were observed on Relay test unit (Doble)/Laptop.

PREPARED BY

CHECKED BY

T. Ghosh

[Signature]

TL 1424459





Certificate No. : T-3359

ELECTRICAL RESEARCH AND DEVELOPMENT ASSOCIATION

(Accredited by the National Accreditation Board for Testing and Calibration Laboratories, Govt. of India)

ERDA Road, Makarpura Industrial Estate, Vadodara-390 010, India.

EPABX : +91 (0265) 2642942, 2642964, 2642377, 3043128 / 29 / 30 / 31 / 33

Fax : +91 (0265) 2638382

E-mail : erda@erda.org


Web : <http://www.erda.org>



TEST REPORT NO.: RP-1617-049429

DATE: 24/01/2017

SHEET 33 OF 34



Test set up photograph for Electrical Fast Transient/Burst Immunity test

PREPARED BY

T. Shreshth

CHECKED BY

[Signature]

TL 1424199





ELECTRICAL RESEARCH AND DEVELOPMENT ASSOCIATION

(Accredited by the National Accreditation Board for Testing and Calibration Laboratories, Govt. of India)

ERDA Road, Makarpura Industrial Estate, Vadodara-390 010, India.

EPABX : +91 (0265) 2642942, 2642964, 2642377, 3043128 / 29 / 30 / 31 / 33

Fax : +91 (0265) 2638382

E-mail : erda@erda.org

Web : http://www.erda.org



TEST REPORT NO.: RP-1617-049429

DATE: 24/01/2017

SHEET 34 OF 34

Your reference -

Platform: ADR24xB-M Sr.No. : 16L245M0001

Model : ADR245B-M-AM-M-0-0-3-0-1-1-0-2-2-H

AUX :- 24-230 VAC/DC CT:- 1A/5A

Cabinet Type :- M14 PT:- 63.5 VAC

Test Report : Connectors : Extra Screws :

Operating Manual : Mounting Clamps :

Operator's Instruction : Battery Isolation Strip :

ASHIDA ELECTRONICS PVT.LTD.
 Wagie Ind Estate, THANE(W) - 400604.
 Corp. Off. Tel: +91-22-25827524/25(M)
 91-22-25827526, 61299124(Board Lines)
 Fax : 91-22-25804262

ASHIDA

Photograph of sample Description mentioned on EUT

PREPARED BY

T. Shuskbz

CHECKED BY

[Signature]

TL 1424339

